



Sequential Module for dust sampling

SENTINEL PM

MAIN CHARACTERISTICS

**Certified by TÜV
in accordance with the
EN12341 and DM60 norms**

Main applications:

- Total particulate matter
- 10, 2.5, 1 micron fractions (PM10, PM2.5, PM1)
- Heavy metals

16 filter capacity

Reduced dimensions
and weight

Operation box for outdoor
use with IP 55 protection
grade

Fixable to wall

Forced ventilation circuit
for safeguarding the
samples' integrity

The SENTINEL PM module combined with the atmospheric sampler Charlie, allows the automated and sequential collections of the atmospheric particulate matters on 47 mm diameter filtering membranes, which are contained in appropriate filterholder cassette.

The 16 filter capacity and the particular realization of a removable system, permit the filter recovering and replacing without interrupting the sampling, and so without predeterminating the periods of time of its operation.

The straight route of the suction tube and the separation of the permanence zone of the filters from the internal or radiant source of heat allows gaining and maintaining the integrity of the samples.

Thanks to its reduced dimensions and weight, Sentinel PM is easy to transport and integrate in the monitoring cabins.



The modularity of the sampling head allows choosing the desired impactor type to operate in accordance with the EN 12341 and USEPA 40 CFR Part 50 methods.

TECHNICAL CHARACTERISTICS

Used supports	Membrane filters 47 mm diam
Autonomy	16 filters
Power supply	220 V 50 Hz
Dimensions mm	400 x 250 x 600 mm (b x b x h)
Box	In fire painted steel
Weight Kg	13 kg
P/N of article	AA99-013-0005P
Roof crossing kit	AA99-013-9906P

* *Facultative options*

